

Granville FS-RN 0W/20

1 Litre, 5 Litre & 20 Litre

PRODUCT DESCRIPTION

Granville FS-RN 0W/20 is a high quality fully synthetic engine oil for use in petrol & diesel engines where RN17 FE is required. The blend of specially selected additives and base oils offer optimal performance and fuel efficiency whilst extending component life.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C5

Renault: RN-17 FE

PRODUCT BENEFITS

- * Excellent fuel economy.
- * Outstanding wear protection.
- * Low Sulphated ash content.

PRODUCT USAGE

Use as recommended by the vehicle manufacturer.

DIRECTIONS FOR USE

As per the vehicle handbook

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place

SHELF LIFE

5 years from date of manufacture

| | |
|-------------------|----------------------|
| Appearance | : Amber Liquid |
| Odour | : Characteristic |
| Solubility | : Insoluble in water |



* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|----------|---------|---------------|
| 1 Litre | 1158 | 5020618011583 |
| 5 Litre | 1159 | 5020618011590 |
| 20 Litre | 1160 | 5020618011606 |



Granville FS-RN 0W/20

1 Litre, 5 Litre & 20 Litre

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 6.9 | <9.3 | |
| Viscosity, CCS -35°C | ASTM D4684 | mPa.s | | 6200 | |
| Total Base Number | ASTM D2896 | mg KOH/g | 7.5 | | |
| HTHS Viscosity | ASTM D4683 | mPa.s | 2.6 | | |
| NOACK Volatility | ASTM D5800 | % | | 11 | |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

